

What is claimed is :

1. An electric double layer capacitor having electrodes which include activated carbon particles and a binder binding said activated carbon particles,
5 wherein a density of said electrodes is in the range of 1.4 g/cm³ to 1.8 g/cm³.
2. The electric double layer capacitor as claimed in claim 1,
10 wherein a specific resistance of said electrodes is in the range of 2.0 Ω cm to 7.0 Ω cm.
3. The electric double layer capacitor as claimed in claim 1,
15 wherein an averaged diameter of said activated carbon particles is in the range of 5 micrometers to 13 micrometers, and a particle size distribution thereof is in the range of 2 micrometers to 20 micrometers.
4. The electric double layer capacitor as claimed in claim 1,
20 wherein said binder contains a fluoro-containing polymer.
5. The electric double layer capacitor as claimed in claim 1,
wherein said binder contains polyvinylidene fluoride.
6. An electric double layer capacitor comprising :

a separator ;

a pair of electrodes separated by said separator, and said electrodes including activated carbon particles and a binder binding said activated carbon particles ; and

5 a pair of collectors separated by said pair of electrodes,
wherein a density of said electrodes is in the range of 1.4 g/cm³ to 1.8 g/cm³.

7. The electric double layer capacitor as claimed in claim 6,
10 wherein a specific resistance of said electrodes is in the range of 2.0 Ω cm to 7.0 Ω cm.

8. The electric double layer capacitor as claimed in claim 6,
15 wherein an averaged diameter of said activated carbon particles is in the range of 5 micrometers to 13 micrometers, and a particle size distribution thereof is in the range of 2 micrometers to 20 micrometers.

9. The electric double layer capacitor as claimed in claim 6,
wherein said binder contains a fluoro-containing polymer.

20 10. The electric double layer capacitor as claimed in claim 6,
wherein said binder contains polyvinylidene fluoride.

11. An electrode including :

activated carbon particles ; and
a binder binding said activated carbon particles,
wherein a density of said electrodes is in the range of 1.4 g/cm³
to 1.8 g/cm³.

5

12. The electrode layer capacitor as claimed in claim 11, wherein a
specific resistance of said electrodes is in the range of 2.0 Ω cm to 7.0 Ω cm.

13. The electrode as claimed in claim 11, wherein an averaged
10 diameter of said activated carbon particles is in the range of 5 micrometers
to 13 micrometers, and a particle size distribution thereof is in the range of
2 micrometers to 20 micrometers.

14. The electrode as claimed in claim 11, wherein said binder
15 contains a fluoro-containing polymer.

15. The electrode as claimed in claim 11, wherein said binder
contains polyvinylidene fluoride.